

AMENDMENTS TO THE CLAIMS

(IN FORMAT COMPLIANT WITH THE REVISED 37 CFR 1.121)

Please cancel claim 12 without prejudice.

1. (CURRENTLY AMENDED) A method for generating a superset ~~pinouts~~ pinout for a family of devices, comprising the steps of:

(A) defining a pinlist for each device within said family of devices;

(B) generating a superset listing of pins from said pinlist;

(C) creating said superset pinout for said family of devices ~~by eliminating from said superset listing of pins to~~ eliminate potential footprint variations within said family of devices ~~with said superset pinout~~; and

(D) marking each pin of said superset pinout associated with each member of said family of devices.

2. (CURRENTLY AMENDED) The method according to claim 1, wherein step (D) further comprises;

customizing ~~said a~~ superset ~~pinout~~ grid according to said superset listing of pins.

3. (CURRENTLY AMENDED) The method according to claim 2, wherein step (D) further comprises:

marking a specific ~~pinout~~ pin in said superset grid for  
each member of said family of devices in response to the  
5 customizing.

4. (ORIGINAL) The method according to claim 1, wherein  
said family of devices comprises devices with combined programmable  
logic and high-speed serial channels.

5. (CANCELED).

6. (PREVIOUSLY PRESENTED) The method according to claim  
1, wherein step (C) further comprises:

eliminating potential layout variations within said  
family of devices with said superset pinout.

7. (PREVIOUSLY PRESENTED) The method according to claim  
1, wherein step (B) further comprises:

combining pins shared by more than one member of said  
family of devices.

8. (ORIGINAL) The method according to claim 1, wherein  
step (C) further comprises:

allocating a pin for each signal in said pinlist.

9. (CURRENTLY AMENDED) The method according to claim 1, wherein step (C) further comprises:

providing a common footprint ~~common~~ to each member of said family of devices.

10. (CURRENTLY AMENDED) The method according to claim 1, wherein step (C) further comprises:

designing a board layout (i) to accommodate more than one member accommodating needs common to members of said family of devices and (ii) to allow for late changes without affecting said board layout and without external components with said superset pinout.

11. (CURRENTLY AMENDED) The method according to claim 1, wherein step (C) further comprises:

limiting each pin of said superset ~~listing of pins~~ pinout to a single function.

12. (CANCEL)

13. (ORIGINAL) The method according to claim 1, wherein step (D) further comprises:

marking one or more pins no-connect for a particular member device.

14. (ORIGINAL) The method according to claim 1, wherein said family of devices comprise programmable logic and high-speed serial channel devices.

15. (ORIGINAL) The method according to claim 1, wherein step (C) further comprises:

allowing for migration of devices within said family of devices.

16. (ORIGINAL) The method according to claim 1, wherein step (C) further comprises:

allowing for migration to higher gate densities.

17. (ORIGINAL) The method according to claim 1, wherein step (C) further comprises:

allowing for migration to increased bandwidth channels.

18. (CURRENTLY AMENDED) The method according to claim 1, wherein step (C) further comprises:

reducing layout and footprint changes on a board  
~~connected between~~ configured to connect to said members of said  
5 family of devices.

19. (CURRENTLY AMENDED) An apparatus ~~comprising~~.

~~means~~ for generating a superset pinouts pinout for a family of devices, comprising:

means for defining a pinlist for each device within said family of devices;

means for generating a superset listing of pins from said pinlist ~~by eliminating layout variations within said family of devices with said superset pinout;~~

means for creating said superset pinout for said family of devices from said superset listing of pins, wherein said superset pinout eliminates layout variations within said family of devices; and

means for marking each pin of said superset pinout associated with each member of said family of devices.

20. (CURRENTLY AMENDED) An apparatus comprising:

a device configured to generate a superset pinouts pinout for a family of devices, wherein (A) said device is further configured to (i) define a pinlist for each device within said family of devices, (ii) generate a superset listing of pins from said pinlist, (iii) create said superset pinout for said family of devices from said superset listing of pins, and (iv) mark each pin of said superset pinout associated with each member of said family of devices, ~~wherein~~ and (B) said superset listing of pins pinout is generated by reducing configured to reduce layout and footprint

changes on a board ~~connected between~~ configured to connect to each member of said family of devices.